



**.025" MICRO QUICK-TWIST
TPO CABLE
IDT FLAT RIBBON CABLE**

SPECIFICATIONS

ENVIRONMENTAL

Temperature Rating: +90°C

MECHANICAL

Insulation: Thermoplastic Olefin Laminated

Conductor: 30 AWG, 7/38 stranded, tinned copper wire

Span Length: Center of flat section to center of flat section
See option below

ELECTRICAL

Voltage Rating: 30V - UL

UL Style No.: 21057

250mm Impedance: 97 ohms, single ended
120 ohms, differential

125mm Impedance: 90 ohms, single ended
115 ohms, differential

CA-68MT-TPO- SPAN

SPAN LENGTH
Blank = 9.84" [250mm]
125 = 4.92" [125mm]



**.025" LAMINIATED MICRO QUICK-TWIST
TPO CABLE
IDT FLAT RIBBON CABLE**

SPECIFICATIONS

ENVIRONMENTAL

Temperature Rating: +90°C

MECHANICAL

Insulation: Thermoplastic Olefin Laminated

Conductor: 30 AWG, 7/38 stranded, tinned copper wire

Span Length: Center of flat section to center of flat section
See option below

ELECTRICAL

Voltage Rating: 30V - UL

UL Style No.: 21057

250mm Impedance: 95 ohms, single ended
120 ohms, differential

125mm Impedance: 90 ohms, single ended
115 ohms, differential

CA-68MTS-TPO- SPAN

SPAN LENGTH
Blank = 9.84" [250mm]
125 = 4.92" [125mm]