



.050" PVC CABLE IDT FLAT RIBBON CABLE

SPECIFICATIONS

ENVIRONMENTAL

Temperature Rating: +105°C

MECHANICAL

Insulation: PVC, gray

Conductor: 28 AWG, 7/36 stranded, tinned copper wire

ELECTRICAL

Voltage Rating: 300V - UL, 300V - CSA

UL Style No.: 2651

CSA Style No.: AWM I A/B FT-1

Impedance: 105 ohms, single ended

145 ohms, differential

CA- IDC-G

CABLE SIZE			
06	15	26	40
08	16	30	50
10	20	34	60
12	24	36	64
14	25	37	72



.050" RAINBOW CABLE IDT FLAT RIBBON CABLE

SPECIFICATIONS

ENVIRONMENTAL

Temperature Rating: +105°C

MECHANICAL

Insulation: SR-PVC

Conductor: 28 AWG, 7/36 stranded, tinned copper wire

ELECTRICAL

Voltage Rating: 300V - UL, 300V - CSA

UL Style No.: 20932

CSA Style No.: AWM I A/B FT-1

Impedance: 98 ohms, single ended

135 ohms, differential

CA- IDC-CC

CABLE SIZE			
09	16	26	50
10	20	34	60
14	24	37	64
15	25	40	